Material Safety Data Sheet **Fabric Master Heavy Duty**

STATEMENT OF HAZARDOUS NATURE: Non-Hazardous according to the criteria of NOHSC Australia

COMPANY

COMPANY	Carpet Cleaners Warehouse
Address	Unit 1/3 Sutherland Street Granville NSW 2142
Telephone	1800 68 68 69
Fax	(02) 8868 0099
Emergency Telephone Number	1800 68 68 69

IDENTIFICATION

PRODUCT NAME	**FABRIC MASTER HEAVY DUTY**
Manufacturer's PRODUCT CODE:	FABRIC MASTER HEAVY DUTY
UN NUMBER	None Allocated
PROPER SHIPPING NAME	None Allocated
DANGEROUS GOODS CLASS	None Allocated
HAZCHEM CODE	None Allocated
POISONS SCHEDULE NUMBER	None Allocated
PACKAGING GROUP	None Allocated
PRODUCT USE	Carpet Cleaner
RISK PHRASES	R22 Harmful if swallowed R36/38Irritating to eyes and skin
SAFETY PHRASES	S1/2 Keep locked up and out of reach of children S23 Do not breathe vapour S24/25 Avoid contact with skin and eyes S26 In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or poisons Information Centre

INGREDIENTS

Ingredient	CAS Number	Proportion	Exposure Limit (Worksafe Australia)
Glycol Ether EB	111-76-2	<10	TWA - 25 ppm (121 mg/m3) Note: (SK) Absorption through the skin may be a significant source of exposure
Anionic Surfactants	mixture	<5	not established
Nonionic Surfactants	mixture	<10	
Isopropanol		<5	
Water		>60	

PHYSICAL DESCRIPTION/PROPERTIES

APPEARANCE & ODOUR	clear liquid, sweet odour

Material Safety Data Sheet **Fabric Master Heavy Duty**

BOILING POINT	100 C
VAPOUR PRESSURE	760 mmHg
SPECIFIC GRAVITY	0.989
FLASH POINT	Not Flammable to boiling point
FLAMMABLE LIMITS	not determined
Solubility in Water	complete

OTHER PROPERTIES

REACTIVITY	not determined
.pH @ 20C	11.0-12.0
Per Cent Volatile	greater than 80%
Bulk Density	0.98 kg/litre

HEALTH HAZARD INFORMATION

ACUTE HEALTH EFFECTS

- SWALLOWED	Swallowing may cause irritation of the gastrointestinal tract. Large amounts may result in headaches, dizziness, nausea may lead liver and kidney damage.
- EYE	Will cause irritation to the eyes. Prolonged exposure may cause eye
- SKIN	Harmful by skin contact. The Glycol Ether EB absorbs through the skin. May cause irritation to the skin.
- INHALED	
CHRONIC HEALTH EFFECTS	Chronic exposure to Glycol Ether EB may cause damage to blood cells, liver or kidney damage. Prolonged skin contact may cause dermatitis.

FIRST AID

SWALLOWED	Do not induce vomiting. If victim is conscious, give larger quantities of water. Never give anything by mouth to an unconscious person. Contact a doctor immediately.
EYE	Hold eyelids open and flush with water for at least 15 minutes. If irritation persists see a doctor.
SKIN	Flush thoroughly with water until no longer slippery. Remove contaminated clothing. Wash before wearing again. If irritation occurs, call a doctor
INHALED	Remove to fresh air. If breathing is difficult call a doctor.
ADVICE TO DOCTOR	Treat symptomatically

Material Safety Data Sheet **Fabric Master Heavy Duty**

PRECAUTIONS FOR USE

EXPOSURE STANDARDS	No exposure standard Allocated for finished product. See ingredient information
ENGINEERING CONTROLS	Use with adequate ventilation
PERSONAL PROTECTION	
.-Respirators	Not normally required. If risk of inhalation in amounts determined to be hazardous based on ingredient information, wear suitable respirator meeting the requirements of AS/NZS 1715/1716 for organic vapours and mists.
.-Gloves	Impervious Neoprene, PVC or rubber gloves are recommended.
.-Eye	Not normally required. If spraying or misting overhead wear goggles or glasses.
.-Clothing	Special clothing not normally required. If process might wet clothing with product solution, then resistant aprons and footwear should be worn.
FLAMMABILITY	NOT FLAMMABLE

SAFE HANDLING INFORMATION

STORAGE & Transport	Not classified as Dangerous goods per code of transportation by road and rail.
STORAGE	Store in a cool, dry place with adequate ventilation. Wash after use. Do Not mix chemicals. Keep away from in compatibles. Keep away from oxidizers.
.-time limits for safe storage	
.-incompatibles	Oxidisers
SPILLS	Absorb with inert material. Sweep or scrape up and containerise.
DISPOSAL	No special. Method. Observe all applicable governmental regulations.
EFFECTS ON THE ENVIRONMENT	Avoid contaminating waterways.
FIRE/EXPLOSION HAZARD	
.-Fire fighting Recommendations and precautions	Normal fire fighting procedures may be used.
.-Personal protection	None allocated
.-Fire Extinguishing Agents	Foam, CO_2. Dry chemical. Water fog. Do NOT use water jets

OTHER INFORMATION

Toxicity	Not determined for this mixture - LD50 Glycol Ether EB : 2400 mg/kg.

Material Safety Data Sheet **Fabric Master Heavy Duty**

Carcinogenic	None known
Ecotoxicity	Not determined for this mixture
Biodegradability	Not determined for this mixture
Chemical Ingredients	All ingredients are registered on the Australia Inventory of Chemical Substances.

CONTACT POINT

AUSTRALIA